



Lusin® Alro OL 202 F

Silicone-free Release Agent for Processing Thermoplastic Resins

Benefits

- For use at mould temperatures up to 200°C (392 °F)
- Also applicable as a lubricant
- Silicone-free
- Water soluble
- NSF registered, conforms to H1 listing requirements
- The formulation is in compliance with European Plastics Regulation No 10/2011

Shelf life

Aerosol: 24 months

Packaging

Aerosol: 400mL with 12 cans per box

Description

Lusin® Alro OL 202 F is a silicone-free release agent for the processing of thermoplastic resins. It is also suitable as a lubricating agent with improved antifriction properties. Due to the conformity to H1 listing requirements and the compliance with European Plastics Regulation No 10/2011, Lusin® Alro OL 202 F can be used as release and antifriction agent for parts that might come into contact with food.

Typical Properties

Appearance of the active ingredient Liquid, yellowish

Application

A fine even film should be applied to the clean mould; especially to edges and undercuts. For cleaning we recommend the use of Lusin® L 21 F as mould cleaning agent and Lusin® Clean L 52 F as degreasing agent. Both products are NSF registered conforming to K1 and K3 listing requirements.

Should subsequent treatment of the parts be required, e.g. metal coating, lacquering, etc. we recommend preliminary tests.

Residues of the release agent are easily removed by rinsing the parts with a mixture of water and cleaner (e.g. Lusin® Clean W 81).

Storage / Handling

Lusin® Alro OL 202 F should be stored in a dry indoor area at room temperature.

For further information on storage, handling, hazards, etc. please refer to safety data sheet.

Further Information

Request information on our complete range of materials for this industry.

Legal Notice

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. Chem-Trend warrants only that its products will meet its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are requested to check that they are in possession of the latest version of this document and Chem-Trend is at their disposal to supply any additional information.