



Lusin® Protect G 32

Wax-based Anticorrosion and Lubricating Agent

Benefits

- Stable red film; resistant to handling
- Lasting protection against corrosion
- Suitable for the use as release agent

Description

Lusin® Protect G 32 is a highly efficient anticorrosion agent that also shows lubricating properties. The delayed generation of the solid protective film enables Lusin® Protect G 32 to penetrate into very fine cracks. The protective film is resistant to handling and starts melting at around 50°C (122 °F).

Typical Properties

Corrosion protection per DIN 50017	No corrosion after 20 h
Salt spray test per DIN 50021 with 5% NaCl-solution	No corrosion after 28 h

Application

Lusin® Protect G 32 is mainly used to protect moulds and dies dedicated for processing thermoplastic resins against corrosion.

Lusin® Protect G 32 only shows maximum anticorrosion properties when applied on dry and clean metal surfaces. For cleaning we recommend the use of Lusin® Clean L 21 F as mould cleaning agent and Lusin® Clean L 11 or Lusin® Clean L 51 as degreasing agent.

Optimal film generation is only ensured if Lusin® Protect G 32 is applied in several thin layers taking particular care to cover edges and undercuts.

Lusin® Protect G 32 can either be removed by the use of cleaning agents like Lusin® Clean L 11 or Lusin® Clean L 51 or by producing parts thus transferring the protective agent to the produced parts.

In terms of subsequent treatment of the produced parts, such as lacquering, printing or gluing, preliminary tests are recommended.

Storage

Lusin® Protect G 32 should be stored in a dry indoor area at room temperature.

For further information on hazards etc. please refer to safety data sheet.

Shelf life

Aerosol and bulk: 24 months

Packaging

Aerosol: 400 mL with 12 cans per box

Further Information

Request information on our complete range of materials for this industry..

Legal Notice

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. Chem-Trend warrants only that its products will meet its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are requested to check that they are in possession of the latest version of this document and Chem-Trend is at their disposal to supply any additional information.